

CA 900-RF



DESCRIPTION

Microphone stand designed for floor standing microphones. 1200mm Floor Standing Long Shaft

- 1200 mm long rigid shaft and short upright shaft connected by a separate, lockable swivel joint allowing adjustments to angle, height and reach.
- Phantom Power Adaptor at the bottom end terminating in a male 3 pin XLR.
- Knuckle joint at tip with Switchcraft Tini Q - 3 (mini xlr) pin female connector.
- A bolt and washer are supplied to secure the short shaft to the SM155 floor mounting shock absorbing base.
- Immune to radio interference from GSM frequencies 800 – 1200MHz

For 'Glossary of Terms' [Click Here](#)

Technical	
Application	For floor standing mounting of microphones.
Impedance	200 Ohms
Termination	Bottom end: Male 3 pin XLR Tip: Switchcraft Tini Q (mini xlr) 3 pin female connector
Finish	Satin black
Dimensions	Long Shaft: 1200mm (48") Short upright Shaft: 350mm (14")
Architects and engineer specifications	1200mm Long rigid shaft and 350mm short upright shaft connected by a separate, lockable swivel joint allowing adjustments to angle, height and reach. A Phantom Power Adaptor at the bottom end and knuckle joint at tip with Switchcraft Tini Q - 3 pin female connector. A bolt and washer are supplied to secure the short shaft to the SM155 floor mounting shock absorbing base. The construction has been tested and passed Clockaudio RF immunity testing for GSM frequencies 800 – 1200MHz. The finish is low reflective Satin Black Long Shaft: 48" (1200mm) Short Shaft: 14" (350mm)

ADDITIONAL IMAGES

