



**MODEL :** GT-402T



## DESCRIPTION

GT-402T is a hand held transmitter microphone.

- The circuitry uses a high stability PLL synthesised UHF transmitter designed for use on licensed free UHF FM 863-865 MHz frequencies (subject to local licensing laws).
- It has 16 programmed preset switchable channels.
- GT-402T is supplied with NiMh rechargeable batteries typically allowing 10 hours usage on a single full charge (16 hours on a typical non recharge alkaline battery).
- Operating range in free air (open field) 100 Metres.
- Erp output:10mW

For 'Glossary of Terms' [Click Here](#)

Technical	
Dimensions	Body diameter 35mm (1.37") Head diameter 51mm (2")
Length	Length 237mm (9.3")
Application	Designed for use with the Guided tour receiver series.
Supplied Accessories	NiMh rechargeable batteries
Weight	285gms
Finish	Black
Architects and engineer specifications	GT402T is a hand held transmitter microphone. The circuitry uses a high stability PLL synthesised UHF transmitter designed for use on licensed free UHF FM 863-865 MHz frequencies (subject to local licensing laws). It has 16 programmed preset switchable channels. GT-402T is supplied with NiMh rechargeable batteries typically allowing 10 hours usage on a single full charge (16 hours on a typical non recharge alkaline battery). Operating range in free air (open field) 100 Metres. Has a detachable module for to allow dynamic or Condenser microphone capsule to be used.

Technical	
	Dimensions: Length 237mm (9.3") Body diameter 35mm (1.37") Head diameter 51mm (2") Weight: 285gms (including battery) RF output:10mW