

GT SET FOUR



The Clockaudio GT SET FOUR guided tour system helps tour groups overcome disturbing background noise and distance from the guide even in noisy surroundings. The system consists of a transmitter, 19 pocket size receivers with rechargeable batteries and a rack mountable or stand alone charger. It is easy to set up and use and operates over a distance of 100 meters. When fully charged the system can be used for 8-10 hours. The system is suitable for in and outdoor guided tours, and can also be used in meetings where one or more interpreters provide real time translation. It accommodates any number of users with additional receivers. The Clockaudio Wireless Tour Guide System is easy to use and requires no installation.

Frequency Range 863-870MHz

Not available in the US and Canada.

Description

Guided tour System comes complete with 19 x GT-400R receivers and 1 x GT-400T transmitter.

- Portable, wireless listening, easy to set up and use. No installation is required.
- Operating distance 100 meters (open field).
- 16 switchable frequencies in Channel 10 (863-870MHz).
- LCD channel display to show the selected channel by up and down button, frequency, battery condition and error code.
- Allows an unlimited number of additional receivers to be used with one transmitter.
- Pocket size, rechargeable wireless transmitters and receivers.
- Fully charged batteries provide 8-10 hours use.
- GT 400T transmitter incorporates MIC. Input and Aux. input allowing audio sources from CD or MP3 player.
- GT 400R receiver includes Aux. Output for connecting an amplifier or active speaker form a wireless receiver system and 3.5mm jack for use with earphones or neck loop.
- Finish: Black.

For 'Glossary of Terms' [Click Here](#)

Specification

Technical	
Application	For use on individuals or group situations such as narration or instructional use on guided tours, museums, Zoos, factories, garden events, language tuition, or any indoor / outdoor activities. Charger complete with 19 x 863 – 870MHz GT400R receivers and 1 x 863 – 870MHz GT400T transmitter.
Frequency Response	70Hz - 15Khz
Power Requirements	Lithium 3.7V 1200mA battery
Operating Temperature	-10° C - 50° C
Finish	Black
Operating Range	> 100M meters
Oscillation Type	PLL Synthesized Control OSC
Carrier Frequency Range	863MHz - 870MHz
Channels	32
Dynamic Range	>80db
T.H.D.	<1%
Dimensions	34.2 x 52.1 x 88 (mm)
Weight	Tx: 75g / Rx: 85g (with Battery)