



Configuration:

- LA-205-01 30 VDC Extension/Replacement Power Supply for LA-140/LT-82 (North America)*
- LA-205-02 30 VDC Extension/Replacement Power Supply for LA-140/LT-82 (Asia, UK)*
- LA-205-03 30 VDC Extension/Replacement Power Supply for LA-140/LT-82 (Euro)*
- LA-205-03 31 VDC Extension/Replacement Power Supply for LA-140/LT-82 (Australia)*

*01, 02, 03, and 04 designation refers to international plug type (type B, G, C, and I) for the power supply.

Product Overview:

The LA-205 is a replacement for the LT-82 power supply or can be used to power an additional two (2) stationary IR radiators. The power supply connects to the transmitter or the radiators via CAT-5 cabling for simple installation. This unit can be specified for North America, Europe or United Kingdom.

Highlights:

- Standard CAT-5 connection – easy and inexpensive
- Available for multiple countries – can be used in many places around the world
- Cat-5 conversion cable included

Includes: One (1) LA-205 30 VDC Extension/Replacement Power Supply for LA-140/LT-82

Product Specification: Replacement/Extension Power Supply for LA-140/LT-82	
Power	
Power Supply Input	100-240 VAC, 50-60 Hz, 1.5 A
Type	In-line switching mode power supply
Power Supply Connector	5.0mm x 2.1mm Barrel
Power Output	30 VDC, 1.5 A, 45 W
Physical	
Width	2.25 in. (6 cm)
Height	1.25 in. (3 cm)
Depth	4.75 in. (12 cm)
Color	Dark Grey
Shipping Weight	2.0 lbs (1.1 kg)
Weight	1.1 lbs. (0.5 kg)
Cord Length	85 in. (216 cm)
Line Cord Length	39 in. (99 cm)

Product Specification: Replacement/Extension Power Supply for LA-140/LT-82	
Environmental	
Temperature - Operation	-10 °C (14 °F) to +40 (104 °F)
Temperature - Storage	-20 °C (-4 °F) to +50 (122 °F)
Relative Humidity	0 to 95% relative humidity, non-condensing
Compliance	
Safety	FCC, Industry Canada, CE, RoHS