

# CP-1050 Direct Drive Turntable



CP-1050 (B) Open



CP-1050 (Y) Open

## Rediscover the Magic of Vinyl

There's never been a better time to rekindle your passion for collecting and listening to records. With the introduction of the CP-1050, Onkyo offers a turnkey solution for audiophile-level analog sound with less hassle and expense. It features a smooth and stable direct drive (there's no belts to replace and less high-frequency noise) controlled by a quartz-lock system to ensure the aluminum platter rotates with utmost precision. The aluminum tonearm ships with a quality MM cartridge, and thanks to an innovative counterweight system and detachable headshell, can also accept most popular aftermarket cartridges. Together with solid MDF deck construction, these elements combine to deliver exceedingly beautiful sound that's both clear and detailed while celebrating the lushness, depth, and warmth so beloved of the analog format. As you would expect from a company that created its first crystal turntable pickup for the CP-1000 back in 1946, every aspect of the design has been painstakingly engineered to deliver audio performance well beyond its suggested price.

### ADVANCED FEATURES

- Built to Deliver Affordable Audiophile-Grade Sound
- Stable Direct-Drive System for Minimal Low-Frequency Cogging Noise
- Customized Brushless DC Motor
- Quartz-Lock Control System for High-Precision Rotation
- Solid Anti-Vibration MDF Cabinet Construction with Black or Yellow Woodgrain Finish
- Die-cast 305 mm Aluminum Platter for Effortlessly Smooth and Stable Rotation

- Wow and Flutter Less than 0.15%
- Signal-to-Noise Ratio Over 60 dB
- Aluminum Static-Balance S-shaped Tonearm
- Moving-Magnet (MM) Cartridge Included
- Detachable Headshell Compatible with Aftermarket Cartridges
- Tonearm Counterweight Supports Range of Cartridge Weights
- Gold-Plated RCA Phono Output Terminals with Dedicated Grounding Post (Cable Included)
- Easy Button-Selectable 33 1/3 and 45 rpm Speeds

- Quickly Spins to Playback Speed Stability
- Includes Detachable Acrylic Dust Cover
- Resonance-Damping Rubber Slipmat Included
- Large Height-Adjustable Anti-Vibration Feet

### CONNECTION FEATURES

- RCA Phono Outputs
- Grounding Post
- AC Inlet

*Note: Phono equalizer not included.*

# CP-1050 Direct Drive Turntable

## Innovative Direct Drive Plays Records Clean and Clear

The enemies of turntable sound quality are vibration and electro-mechanical noise picked up by the stylus. Instead of a high-torque motor, Onkyo deploys a stable low-torque design that significantly reduces cogging noise, which can noticeably obscure low-frequency sound. And unlike belt-driven turntables that use fast electric motors, the direct-drive CP-1050 avoids the problem of high-frequency distortion. Combined with a precision quartz-lock control system and quality bearings, this liquid-smooth drive provides a clearer window on the soul of your music.

## Die-cast Aluminum Platter

Another weapon in the war against distortion is the heavy die-cast aluminum platter. As well as combating unwanted vibration, the extra inertia assists with rotation stability and keeps the audio pitch from fluctuating. Your LPs are protected by a quality rubber slipmat, which also works to absorb minute resonances from the turntable.

## Quality Tonearm and Cartridge

At the business end of the aluminum tonearm is a detachable headshell that (together with an adjustable counterweight system) supports a range of aftermarket cartridges between 5 g and 10 g. The supplied MM cartridge does a brilliant job of capturing the depth and breadth of any track with an exceptionally wide frequency response and signal-to-noise ratio of over 60 dB—right up there with more costly decks. All design elements combine to produce such open and detailed analog sound you'll be finding any excuse to go digging in the crates.

## Effective Anti-Vibration Design

The turntable base is constructed from solid MDF (Medium-Density Fiberboard) and sits on four height-adjustable anti-vibration feet. Together with the smooth direct-drive motor, the rigid structure tames resonances so you can enjoy clean playback throughout the entire frequency spectrum.

## Selectable Rotation Speeds

Changing rotation speeds from 33 1/3 to 45 rpm and vice versa is simple—just use the button on the top of the deck. The platter quickly reaches playback stability when changing rotation speeds and when spinning up from stop.

## Good Looks, Great Build

Aesthetically, the CP-1050 is a pleasing blend of '70s retro and clean, contemporary style; a choice of black or yellow woodgrain finishes contrasting nicely with the gleaming alloy tonearm and polished metal trim on the top of the deck. The player also includes a detachable acrylic dust cover, and makes the perfect centerpiece for stereo systems of any vintage.

## Top-Shelf Connections

On the rear panel are two gold-plated pin-type RCA phono terminals to output the left and right channel signals to your external phono preamp, stereo amplifier, or A/V receiver. There's also a dedicated grounding post to eliminate hum.

## Ready to Roll Right Out of the Box

The CP-1050 ships with everything needed to play vinyl on your existing stereo system (just be sure to check your receiver has phono inputs before purchase). Install the cartridge, set the tracking pressure as specified in the product manual, connect the turntable using the supplied cable, and you're ready to relive the magic of vinyl in all its glory.



## SPECIFICATIONS

### Turntable Section

Drive Method	Direct-Drive
Turntable Type	305 mm Die-cast Aluminum
Turning Speed	33 1/3 / 45 rpm
Motor Type	Brushless DC
Starting Torque	>1.0 kgf-cm
Brake	Electronic Brake
Wow and Flutter	0.15% or Less at 33 1/3 rpm
Signal-to-Noise Ratio	>60 dB

### Tonearm Section

Type	Static-balanced, S-shaped
Headshell	Detachable
Headshell Weight	10 g
Effective Arm Length	230 mm
Overhang	15 mm
Applicable Cartridge Weight Range (Including Headshell)	15–20 g
Tracking Error Angle	Within 3°
Anti-Skating Range	0–3 g
Stylus Pressure Adjustment Range	0–4 g

### Cartridge Section

Cartridge Type	Moving-Magnet (MM)
Output Voltage	2.5 mV±3 dB (1 kHz at 3.54 cm/Sec.)
Channel Balance	<2.5 dB
Load Resistance	47 kΩ
Cartridge Weight	5 g
Replacement Stylus	DN-105ST
Frequency Response	0±3 dB (10 kHz, Based on Value at 1 kHz)
Channel Separation	>18 dB (at 1 kHz)

### General

Power Supply	AC 220–240 V~, 50/60 Hz
Power Consumption	6 W
Standby Power Consumption	0.4 W
Dimensions (W x H x D)	450 x 158 x 367.5 mm
Weight	8.6 kg

### CARTON

Dimensions (W x H x D)	542 x 243 x 465 mm
Weight	11.2 kg

### Supplied Accessories

- Instruction manual • RCA audio cable • Dust cover
- Adapter for 17 cm 45 rpm records • AC cord



Due to a policy of continuous product improvement, Onkyo reserves the right to change specifications and appearance without notice. All trademarks and registered trademarks are the property of their respective holders.

**ONKYO**

Onkyo & Pioneer Corporation Kitahama Chuo Bldg. 2-2-22 Kitahama, Chuo-ku, Osaka 541-0041 JAPAN <http://www.onkyo.com/>  
 Pioneer & Onkyo Europe GmbH Liegnitzerstrasse 6, 82194 Grobenzell, GERMANY Tel: 49-8142-4208-10 Fax: 49-8142-4208-202 <http://www.eu.onkyo.com/>  
 Pioneer & Onkyo Europe GmbH (UK Branch) Meridian House, Ground floor, 69-71 Clarendon Road, Watford, Hertfordshire, WD17 1DS UNITED KINGDOM  
 Tel: +44-871-200-1996 Fax: +44-871-200-1995 <http://www.onkyo.co.uk/>  
 Pioneer & Onkyo Marketing Asia Ltd. Unit 1033, 10/F, Star House, No. 3, Salisbury Road, Tsim Sha Tsui, Kowloon, Hong Kong, CHINA Tel: 852-2429-3118 Fax: 852-2428-9039  
<http://www.hk.onkyo.com/> (Hong Kong) <http://www.cn.onkyo.com/> (Mainland)