

## DLA series

DLA4-80, DLA6-80,  
DLA600

amplifier accessories

Multi-channel line adaptors permit the use of stereo and multi-channel low impedance amplifiers in 100V/70V applications keeping the best sound quality and ensuring maximum power match and amplifiers' load stability.

### Key features

- 2, 4 and 6 channel 100V/70V line adaptors
- Excellent frequency response for optimal audio performance even in the low frequencies band
- Nominal input power handling (DLA4-80 and DLA6-80) : 80 W RMS/4 ohms
- Nominal input power handling (DLA600) : 80/150/300 W RMS/4 ohms
- EUROBLOCK INPUT and OUTPUT connectors
- 1 RU

### DLA high quality approach

DLA series uses the best audio autotransformers on the professional audio market.

The use of high quality units, allow amplifiers to drive 100V/70V lines no matter what the frequency band of the input signal.

Hence, amplifiers' possible output saturation is eliminated, thus avoiding the use of internal or external high pass filters that unnecessarily affect final sound quality.



Product

Tech. Characteristics	DLA600	DLA4-80	DLA6-80
Input power (nominal)	80/150/300W	80W	80W
Input impedance at nominal power	4Ω	4Ω	4Ω
Output voltages	70/100V	70/100V	70/100V
Frequency response (-3dB)	20Hz÷30kHz	20Hz÷30kHz	20Hz÷30kHz
Dimensions (mm)	482,6 x 266,5 x 44	482,6 x 266,5 x 44	482,6x266,5x44mm
Weight	12kg	8,42kg	11,36kg

### Applications

- Multi-zone and stereo long wire run background and foreground facilities (70/100V lines)

### Best choice amplifiers

Every DLA model has been developed to match the following stereo and multi-channel amplifiers:

- **DLA4-80**: MPA4-80R, NZA4-70
- **DLA6-80**: MPA6-80R, NZA6-70
- **DLA600**: DPA600, XPA3000, MPA4-150R, MPA6-150R, MPA4-400R, NZA4-180, NZA6-180